



# HP Latex 800 W Printer

Win high-value jobs with white ink and productive printing—and sharpen your sustainability edge



## Expand into white, produce the highest value jobs

- Extend your portfolio into high-margin stickers and window graphics with the whitest white.<sup>1</sup>
- Print white without complexity—automatic recirculation and printhead cleaning reduce manual purging.
- Deliver vivid colors at high speed, get striking contrast using pure blacks, and expect sharp 4-point text.
- Choose from a wide application range covering banners/textiles/poster paper, canvas, wallpaper, and vinyl.

## Robust, smart, and productive printing

- Drive high productivity with saturated color at speeds up to 388 ft<sup>2</sup>/hr outdoor<sup>2</sup>, easy spindle-less loading.
- Control print operations virtually anytime, anywhere with HP PrintOS tools, and grow with HP Learn trainings.
- Work fast processing reprints and multi-copy jobs with a smart front panel, and store up to 100 jobs.
- Help reduce running costs with cost-effective 3-liter HP ink cartridges, changed while the printer runs.

## GO BEYOND—Lead with environmental certifications<sup>3</sup>

- Contribute to a comfortable<sup>4</sup> working environment with water-based HP Latex Ink technology.
- Differentiate your business with environmental certifications<sup>3</sup>—including UL ECOLOGO<sup>5</sup> and EPEAT.<sup>6</sup>
- Access the most sensitive spaces with odorless prints<sup>4</sup> and compatibility with a wide range of alternative substrates.<sup>7</sup>
- Reduce your plastics consumption with carton-based cartridge<sup>8</sup> and labelless supplies; free recycling via HP Planet Partners.<sup>9</sup>

For more information, please visit <https://www.hp.com/go/latex800series>

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at <https://lkc.hp.com/>

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: <http://www.hp.com/learn/ds>

<sup>1</sup> Whitest white based on ISO/DIS 23498 compared to competitive alternatives using solvent and UV technologies under \$50,000 USD as of May, 2020. Test performed on black opaque self-adhesive vinyl (L\*:4.16 – a:0.48-b:2.34) with 160% UF printmode using HP 873 3-liter White Latex Ink Cartridge. Visual opacity = 91%.

<sup>2</sup> Outdoor mode (Banner) 4-pass, 100%. Based on internal HP testing in September 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.

<sup>3</sup> Based on internal competitive analysis with public information. Applicable to HP Latex technology compared to competitive large format printing alternatives using solvent and UV technologies. See individual product data sheets for more information at <https://hp.com/go/latex>

<sup>4</sup> Applicable to HP Latex Inks. Based on sensory evaluations conducted by Odournet, done according to VDI Guideline 3882 where 832 and 873 inks were characterized as "weak" in odor intensity and "neutral" for hedonic tone. There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

<sup>5</sup> UL ECOLOGO® Certified HP 832, HP 872, HP 873, and 882 Latex Inks and HP 864, 865, 866, 867, 869, and 870 PageWide XL Inks meet a range of stringent human health and environmental considerations. Verified as of the publishing date in September 2023. For more details, please refer to the UL ECOLOGO® database at <https://spot.ul.com/main-app/products/catalog/> or see <https://www.ul.com/EL>

<sup>6</sup> Applicable to select HP Latex printers. EPEAT registered where applicable/supported. See <https://epeat.net> for registration status by country.

<sup>7</sup> HP applications experts have evaluated the catalog of media listed in the HP Media Locator based on internal criteria to identify those that provide alternative solutions with certain environmental benefits compared to the typical media within the same application type. The information in media locator is provided by the media substrate vendors. HP is not responsible for the veracity of the information from third-party companies published on the HP website. See <https://www.hp.com/go/mediasolutionslocator>

<sup>8</sup> Applicable to HP 832. Plastic reduction based on moving from plastic ink cartridge to cardboard ink cartridges, with annual manufacturing saving of 33 tons of plastic based on average units of HP 831 and HP 831A ink cartridges from 2018 to 2020.

<sup>9</sup> Program availability varies. For details, see <https://hp.com/hprecycle>

Technical specifications

Print	
Printing modes	1313 ft²/hr - Max Speed (1-pass) 388 ft²/hr - High Speed (4-pass) 269 ft²/hr - Production Fast (6-pass) 215 ft²/hr - Production Quality, Textiles and Backlits (8-pass) 183 ft²/hr - High Saturation (12-pass) 151 ft²/hr - High Saturation Backlits and Textiles (14-pass) 183 ft²/hr - White Spot (60%) 99 ft²/hr - White Overflood (60%) 32 ft²/hr - White Underflood (100%) 22 ft²/hr - 3 Layers Day & Night (160%) <sup>1</sup>
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	9 (black, cyan, light cyan, light magenta, magenta, yellow, white, HP Latex Optimizer, HP Latex Overcoat)
Cartridge size	3 L
Printheads	10 (2 cyan/black, 2 magenta/yellow, 2 light cyan/light magenta, 2 white, 1 HP Latex Optimizer, 1 HP Latex Overcoat)
Long-term print-to-print95% of colors ≤ 1.5 dE2000 <sup>2</sup> repeatability	
Media	
Handling	Roll feed, take-up reel, wiper roller <sup>3</sup> , media saver, automatic horizontal cutter (for vinyl, banner and canvas <sup>4</sup> , paper-based media, and film)
Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles <sup>5</sup>
Roll size	16.5 to 64-in rolls (23 to 64-in rolls with full support)
Maximum roll weight	121 lb
Maximum roll diameter	9.8 in
Thickness	Up to 19.7 mil
Applications	
Banners; Displays; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Stickers	
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (W x D x H)	
Printer	101.7 x 34.1 x 55.2 in
Shipping	108.4 x 43.3 x 65.6 in
Operating area	110 x 82.7 in
Weight	
Printer	661 lb
Shipping	976 lb
What's in the box	
HP Latex 800 W Printer, printheads, maintenance cartridge, printer stand, take-up reel, media feed accessory, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor	
Environmental ranges	
Operating temperature	59 to 86°F
Operating humidity	20 to 80% RH (non-condensing)
Acoustics	
Sound pressure	60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)
Sound power	7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)
Power	
Consumption	1.5-2.5 kW (5 kW peak) (printing), 105 W (ready), <4.7 W <sup>6</sup> (sleep) (<24 W <sup>7</sup> with DFE), <0.25 W (off)
Requirements	Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 16 A max per power cord
Certification	
Safety	IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC)
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC)
Environmental	ENERGY STAR®, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, UL ECOLOGO
Warranty	
One-year limited hardware warranty	

Ordering information

Product	
3XD61A	HP Latex 800 W Printer
Accessories	
21V10A	HP Latex 600/700/800 User Maintenance Kit
421S3A	HP Latex Media Feed Accessory
7HR16A	HP Latex 700/800 Textile Kit Accessory
7HR18A	HP Latex 700/800 Ink Collector Foams Kit
7HR19A	HP Latex 630/700/800 Media Loading Accessory
T7U73A	HP Latex 500/700/800 Wiper Roller
Original HP printing supplies	
4UU93A	HP 836 White Latex Printhead
4UU94A	HP 836 Optimizer Latex Printhead
4UV62A	HP 873 3-liter White Latex Ink Cartridge
4UV84A	HP 873 3-liter Black Latex Ink Cartridge
4UV85A	HP 873 3-liter Cyan Latex Ink Cartridge
4UV86A	HP 873 3-liter Magenta Latex Ink Cartridge
4UV87A	HP 873 3-liter Yellow Latex Ink Cartridge
4UV88A	HP 873 3-liter Light Cyan Latex Ink Cartridge
4UV89A	HP 873 3-liter Light Magenta Latex Ink Cartridge
4UV90A	HP 873 3-liter Optimizer Latex Ink Cartridge
4UV91A	HP 873 3-liter Overcoat Latex Ink Cartridge
4UV95A	HP 836 Black/Cyan Latex Printhead
4UV96A	HP 836 Magenta/Yellow Latex Printhead
4UV97A	HP 836 Light Cyan/Light Magenta Latex Printhead
4UV98A	HP 836 Overcoat Latex Printhead
4UU96A	HP 836 Latex Maintenance Cartridge
Original HP large format printing materials	
HP PVC-free Wallpaper (UL GREENGUARD GOLD Certified <sup>8</sup> , FSC® certified <sup>9</sup> , meets AgBB criteria <sup>10</sup> )	
HP Photo-realistic Poster Paper	
HP Premium Satin Canvas	
HP Prime Matte Air GP (REACH compliant <sup>11</sup> )	
HP Premium Removable Gloss Adhesive Vinyl (REACH compliant <sup>11</sup> )	

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support	
U13DDE	HP 2 year Next Business Day with Defective Media Retention
U13DJE	HP 3 year Next Business Day with Defective Media Retention
U13DNPE	HP 1 year Post Warranty Next Business Day with Defective Media Retention
U13DTPE	HP 2 year Post Warranty Next Business Day with Defective Media Retention

<sup>1</sup> Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects.  
<sup>2</sup> The color variation between printed jobs has been measured at 12 pass mode on vinyl media. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 1.5 dE2000. Backlit substrates measured in transmission mode may yield different results.  
<sup>3</sup> Wiper roller is an optional accessory.  
<sup>4</sup> Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test.  
<sup>5</sup> Textile Kit Accessory required for long runs of textile and porous textile.  
<sup>6</sup> Excluding Type 2 DFE (Digital Front End) as defined in Energy Star® Product Specification for Imaging Equipment version 3.1.  
<sup>7</sup> Total power measured in sleep mode including the Digital Front End contained on the product.  
<sup>8</sup> UL GREENGUARD Gold Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <http://www.ul.com/gg> or <http://www.greenguard.org>  
<sup>9</sup> Trademark license code FSC-C1 15319.  
<sup>10</sup> With HP Latex Inks, prints meet AgBB criteria for health-related evaluation of VOC emissions. See <http://umweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building>  
<sup>11</sup> This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.

MAK

PRINTING SOLUTIONS

ماك لحلول الطباعة

02 33 77 6750 - 02 33 77 6751

0100 171 46 44 - 0100 4300 842

011 55 8 99 300 - 011 55 8 99 311

info@makprinteg.com

شارع الزهور - حدائق الأهرام - الرحمة - القاهرة

www.makprinteg.com

@ MAK.PRINTING

Instagram

Facebook